

# FAL GTX150BOAY



Reference: 268004

















Sizes: 35 - 48

Normative:

EN ISO 20345:2022 / A:1:2024

S7S+HI+CI+SR+HRO+FO+LG

## SPECIFICATIONS

-  ESD / Dissipate electrostatic loads
-  Compression 15KN
-  Impact 200J
-  Closed buttress
-  Slip resistance
-  PS / Perforation resistance  $\geq 1100\text{N}$ . Non-Metallic. Punch 3mm
-  CI / Cold insulation of outsole complex
-  HI / Heat insulation of outsole complex
-  E / Energy absorption of heel up to 20J
-  WR / Water resistance of whole footwear
-  A / Antestatic footwear
-  HRO / Resistant to hot contact
-  SR / Slip resistance on ceramic tile floor with glycerine
-  WPA / Resistant to water penetration and absorption
-  FO / Hydrocarbon resistant sole
-  LG / Ladder grip

## DESCRIPTION

### UPPER:

Water-repellent nubuck leather and cordura-type textile.

### SOLE:

Vibram® rubber outsole and polyurethane midsole.

### PROTECTION ELEMENTS:

Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

### LINING:

Gore-Tex® waterproof + breathable membrane

### ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable

### CLOSURE:

BOA® Fit system.