

FAL GTX15Y



Reference: 266004

Sizes: 35 - 48

Normative:

EN ISO 20345:2022 / A:1:2024

S7S+HI+CI+SR+HRO+FO+LG

SPECIFICATIONS



ESD / Dissipate electrostatic loads



No Metallic Pieces



Compression 15KN



Impact 200J



Closed buttress



Closed buttress



PS / Perforation resistance $\geq 1100\text{N}$. Non-Metallic. Punch 3mm



CI / Cold insulation of outsole complex



HI / Heat insulation of outsole complex



E / Energy absorption of heel up to 20J



WR / Water resistance of whole footwear



A / Antestatic footwear



HRO / Resistant to hot contact



SR / Slip resistance on ceramic tile floor with glycerine



WPA / Resistant to water penetration and absorption



FO / Hydrocarbon resistant sole



LG / Ladder grip

DESCRIPTION

UPPER:

Water-repellent nubuck leather and cordura-type textile.

SOLE:

Vibram® rubber outsole and polyurethane midsole.

PROTECTION ELEMENTS:

Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

LINING:

Gore-Tex® waterproof + breathable membrane

ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable

CLOSURE:

Water-repellent laces.