

FAL HR200CR

Reference: 781309

Sizes: 35 - 48

Normative:

EN ISO 20345:2022 / A:1:2024

S3S+HI+CI+CR+SC+SR+HRO+FO+LG

SPECIFICATIONS

| | |
|--|--|
| | ESD / Dissipate electrostatic loads |
| | No Metallic Pieces |
| | Compression 15KN |
| | Impact 200J |
| | Closed buttress |
| | Slip resistance |
| | PS / Perforation resistance $\geq 1100N$. Non-Metallic. Punch 3mm |
| | CI / Cold insulation of outsole complex |
| | HI / Heat insulation of outsole complex |
| | E / Energy absorption of heel up to 20J |
| | A / Antestatic footwear |
| | CR / Cut resistance |
| | HRO / Resistant to hot contact |
| | SR / Slip resistance on ceramic tile floor with glycerine |
| | WPA / Resistant to water penetration and absorption |
| | FO / Hydrocarbon resistant sole |

DESCRIPTION**UPPER:**

Water-repellent textile resistant to blade cut resistant level 5 (EN 388,6.2.)

SOLE:

Rubber outsole and polyurethane midsole.

PROTECTION ELEMENTS:

Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

LINING:

Breathable and abrasion resistant fabric.

ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

CLOSURE:

Laces.