SOLDADOR

FAL HR400

CARBON FREE

Reference: 250109
Sizes: 35 - 48
Normative:
EN ISO 20349-2:2017 / A:1:2020
S3S+HI+CI+SR+HRO+FO+LG+WG

SPECIFICATIONS

- ESD / Dissipate electrostatic loads
- No Metallic Pieces
- Microfiber
- Compression 15KN
- Impact 200J
- Closed buttress
- Slip resistance
- PS / Perforation resistance ≥1.100N. Non-Metallic. Punch 3mm
- CI / Cold insulation of outsole complex
- HI / Heat insulation of outsole complex
- E / Energy absortion of heel up to 20J
- A / Antestatic footwear
- HRO / Resistant to hot contact
- SR / Slip resistance on ceramic tile floor with glycerine
- WPA / Resistant to water penetration and absorpion
- FO / Hydrocarbon resistant sole
- LG / Ladder grip
- WG / Welding footwear

DESCRIPTION

UPPER:
Microfiber resistant to welding splash.

SOLE:
Rubber outsole and polyurethane midsole.

PROTECTION ELEMENTS:
Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

LINING:
Breathable and abrasion resistant fabric.

ERGONOMIC INSOLE:
Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

CLOSURE:
Velcro.