

**FAL HR400**

**Reference:** 250109



















**Sizes:** 35 - 48

**Normative:**

EN ISO 20345:2022 / A:1:2024

S3S+HI+CI+SR+HRO+FO+LG+WG

**SPECIFICATIONS**

	ESD / Dissipate electrostatic loads
	No Metallic Pieces
	Microfiber
	Compression 15KN
	Impact 200J
	Closed buttress
	Slip resistance
	PS / Perforation resistance $\geq 1100N$ . Non-Metallic. Punch 3mm
	CI / Cold insulation of outsole complex
	HI / Heat insulation of outsole complex
	E / Energy absorption of heel up to 20J
	A / Antestatic footwear
	HRO / Resistant to hot contact
	SR / Slip resistance on ceramic tile floor with glycerine
	WPA / Resistant to water penetration and absorption
	FO / Hydrocarbon resistant sole
	LG / Ladder grip
	WG / Welding footwear

**DESCRIPTION****UPPER:**

Microfiber resistant to welding splash.

**SOLE:**

Rubber outsole and polyurethane midsole.

**PROTECTION ELEMENTS:**

Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

**LINING:**

Breathable and abrasion resistant fabric.

**ERGONOMIC INSOLE:**

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

**CLOSURE:**

Velcro.