

FAL HR600

Referencie: 249905

Sizes: 35 - 48

Normative:

EN ISO 20345:2022 / A:1:2024

S3S+HI+CI+SC+SR+HRO+FO+LG

SPECIFICATIONS

	ESD / Dissipate electrostatic loads
	Compression 15KN
	Impact 200J
	Closed buttress
	Slip resistance
	PS / Perforation resistance $\geq 1100N$. Non-Metallic. Punch 3mm
	CI / Cold insulation of outsole complex
	HI / Heat insulation of outsole complex
	E / Energy absorption of heel up to 20J
	A / Antestatic footwear
	HRO / Resistant to hot contact
	SR / Slip resistance on ceramic tile floor with glycerine
	WPA / Resistant to water penetration and absorption
	SC / Scuff cap abrasion
	FO / Hydrocarbon resistant sole
	LG / Ladder grip

DESCRIPTION**UPPER:**

Water-repellent leather.

SOLE:

Rubber outsole and polyurethane midsole.

PROTECTION ELEMENTS:

Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

LINING:

Breathable and abrasion resistant fabric.

ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

CLOSURE:

Quick-release buckle.