

# FAL HR8000



**Reference:** 249609

**Sizes:** 35 - 48

**Normative:**

EN ISO 20345:2022 / A:1:2024  
S3S+HI+CI+SR+HRO+FO+LG



## SPECIFICATIONS

	ESD / Dissipate electrostatic loads
	No Metallic Pieces
	Compression 15KN
	Impact 200J
	Closed buttress
	Slip resistance
	PS / Perforation resistance $\geq 1100\text{N}$ . Non-Metallic. Punch 3mm
	CI / Cold insulation of outsole complex
	HI / Heat insulation of outsole complex
	E / Energy absorption of heel up to 20J
	A / Antestatic footwear
	HRO / Resistant to hot contact
	SR / Slip resistance on ceramic tile floor with glycerine
	WPA / Resistant to water penetration and absorption
	FO / Hydrocarbon resistant sole
	LG / Ladder grip

## DESCRIPTION

### UPPER:

Water-repellent leather.

### SOLE:

Rubber outsole and polyurethane midsole.

### PROTECTION ELEMENTS:

Non-metallic Vincap<sup>®</sup> toe cap and perforation resistant (3 mm nail) textile insole.

### LINING:

Breathable and abrasion resistant fabric.

### ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

### CLOSURE:

Slip-on boot.