

# FAL HR900PLUS



**Reference:** 248709

**Sizes:** 35 - 48

**Normative:**

EN ISO 20345:2022 / A:1:2024

S7S+HI+CI+SC+SR+HRO+FO+LG

## SPECIFICATIONS

	ESD / Dissipate electrostatic loads
	No Metallic Pieces
	Compression 15KN
	Impact 200J
	Closed buttress
	Slip resistance
	PS / Perforation resistance $\geq 1100N$ . Non-Metallic. Punch 3mm
	CI / Cold insulation of outsole complex
	HI / Heat insulation of outsole complex
	E / Energy absorption of heel up to 20J
	WR / Water resistance of whole footwear
	A / Antestatic footwear
	HRO / Resistant to hot contact
	SR / Slip resistance on ceramic tile floor with glycerine
	WPA / Resistant to water penetration and absorption
	SC / Scuff cap abrasion
	FO / Hydrocarbon resistant sole
	LG / Ladder grip

## DESCRIPTION

### UPPER:

Water-repellent suede leather and water-repellent cordura-type textile.

### SOLE:

Rubber outsole and polyurethane midsole.

### PROTECTION ELEMENTS:

Non-metallic Vincap<sup>®</sup> toe cap and perforation resistant (3 mm nail) textile insole.

### LINING:

Gore-Tex<sup>®</sup> waterproof + breathable membrane.

### ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

### CLOSURE:

Water-repellent laces.