

FAL HT1000FZ



GORE-TEX
EXTRAGUARD
TECHNOLOGY

HYDRATECH
BREATHABLE WATERPROOF COMFORT

-50°



















Reference: 243433

Sizes: 35 - 48

Normative:

EN ISO 20345:2022 / A:1:2024
S7S+CI+SC+SR+FO+LG

SPECIFICATIONS

-  ESD / Dissipate electrostatic loads
-  No Metallic Pieces
-  Resistant -50C°
-  Compression 15KN
-  Impact 200J
-  Closed buttress
-  Slip resistance
-  PS / Perforation resistance ≥ 1100 N. Non-Metallic. Punch 3mm
-  CI / Cold insulation of outsole complex
-  E / Energy absorption of heel up to 20J
-  A / Antestatic footwear
-  SR / Slip resistance on ceramic tile floor with glycerine
-  WPA / Resistant to water penetration and absorption
-  SC / Scuff cap abrasion
-  FO / Hydrocarbon resistant sole
-  LG / Ladder grip

DESCRIPTION

UPPER:

Textile with built-in Gore-Tex Extraguard® technology.

SOLE:

Double density polyurethane.

PROTECTION ELEMENTS:

Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

LINING:

Gore-Tex® waterproof + breathable membrane with thermal isolation.

ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

CLOSURE:

Slip-on boot.