

FAL IPR100V



Reference: 270806

Sizes: 35 - 48

Normative:

EN ISO 20345:2022 / A:1:2024

S3S+CI+SC+SR+FO+LG



SPECIFICATIONS

- ESD / Dissipate electrostatic loads
- No Metallic Pieces
- Microfiber
- Compression 15KN
- Impact 200J
- Closed buttress
- Slip resistance
- PS / Perforation resistance $\geq 1100\text{N}$. Non-Metallic. Punch 3mm
- E / Energy absorption of heel up to 20J
- CI / Cold insulation of outsole complex
- A / Antestatic footwear
- SR / Slip resistance on ceramic tile floor with glycerine
- WPA / Resistant to water penetration and absorption
- SC / Scuff cap abrasion
- FO / Hydrocarbon resistant sole
- LG / Ladder grip

DESCRIPTION

UPPER:

Water-repellent textile.

SOLE:

Double density polyurethane.

PROTECTION ELEMENTS:

Non-metallic Vincap[®] toe cap and perforation resistant (3 mm nail) textile insole.

LINING:

Breathable and abrasion resistant fabric.

ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable

CLOSURE:

Velcro.