

# FAL IPR70Y



**Reference:** 273104

**Sizes:** 35 - 48
















**Normative:**

**EN ISO 20345:2022 / A:1:2024**

**S3S+CI+SC+SR+FO+LG**



## SPECIFICATIONS

-  ESD / Dissipate electrostatic loads
-  No Metallic Pieces
-  Compression 15KN
-  Impact 200J
-  Closed buttress
-  Slip resistance
-  PS / Perforation resistance  $\geq 1100\text{N}$ . Non-Metallic. Punch 3mm
-  E / Energy absorption of heel up to 20J
-  CI / Cold insulation of outsole complex
-  A / Antestatic footwear
-  SR / Slip resistance on ceramic tile floor with glycerine
-  WPA / Resistant to water penetration and absorption
-  SC / Scuff cap abrasion
-  FO / Hydrocarbon resistant sole
-  LG / Ladder grip

## DESCRIPTION

### UPPER:

Water-repellent textile.

### SOLE:

Double density polyurethane.

### PROTECTION ELEMENTS:

Non-metallic Vincap® toe cap and perforation resistant (3 mm nail) textile insole.

### LINING:

Breathable and abrasion resistant fabric.

### ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable

### CLOSURE:

Laces.