

FAL PWT900LT
















Reference: 872303

Sizes: 36 - 49

Normative:

EN ISO 20347:2022 / A:1:2024
O7S+SR+CI+HI+HRO+FO+LG

SPECIFICATIONS

-  Closed buttress
-  Slip resistance
-  PS / Perforation resistance $\geq 1100\text{N}$. Non-Metallic. Punch 3mm
-  CI / Cold insulation of outsole complex
-  HI / Heat insulation of outsole complex
-  E / Energy absorption of heel up to 20J
-  WR / Water resistance of whole footwear
-  A / Antestatic footwear
-  HRO / Resistant to hot contact
-  SR / Slip resistance on ceramic tile floor with glycerine
-  WPA / Resistant to water penetration and absorption
-  FO / Hydrocarbon resistant sole
-  LG / Ladder grip

DESCRIPTION

UPPER:

Water-repellent full-grain leather.

SOLE:

Rubber outsole and EVA midsole.

PROTECTION ELEMENTS:

Perforation resistant (3 mm nail) textile insole.

LINING:

Gore-Tex® waterproof + breathable membrane

ERGONOMIC INSOLE:

Made of polyurethane, breathable, anti-odor, anti-bacterial and removable.

CLOSURE:

Water-repellent Laces.